

ABBEY

ABBEY

Product Type	Multi Level Loop
Fiber Composition	100% Olefin
Dye Method	Solution Dyed
Pile Weight	750 g/m ² (22 oz/yd ²)
Number of Tufts	197000/m ²
Machine Gauge	1/10"
Primary Backing	Non-Woven
Secondary Backing	StableShield-100% Vinyl
Tile Size	50 cm x 50 cm (19.6" x 19.6")
Pile Height	4.2 mm 0.165 inch
Total Tile Height	7.2 mm 0.283 inch
Pile Treatment	Walk Of Fame (Optional)
Recommended Installation	Quarter Turn or Brick



WALK
OF FAME

Giving your carpets a boost of soil-resisting properties with Walk of Fame. An anti-soiling treatment that increases the lifespan of your carpet. Technology meets practicality with this dirt-repelling treatment.



SPECIFICATIONS



PERFORMANCE SPECIFICATION

VOC EMISSION	ASTM D5116-06	<0.5 mg/m ² /hour (CRI GLP)
FLAMMABILITY	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
REACTION TO FIRE	EN ISO 9239-1:2002	Dfl-s1
STATIC PROPENSITY	ISO 6356	0.2 kV
COLOR FASTNESS	AATCC/16	5/5 on Grey Scale
THERMAL RESISTANCE	ISO 8302	.04m ² K/W
IMPACT SOUND INSULATION	ISO 140-8	ΔLw 23dB
SOUND ABSORPTION LEVEL	EN ISO 11654	αw: 0.15(H)
SOILING PROPENSITY	ASTM D 6540-00	4
DIMENSIONAL STABILITY	EN 986	< 0.20%
CASTOR CHAIR TEST	DIN 54324	R ≥ 2.4



WEAR
STABILITY
CASTOR CHAIR
COMPATIBILITY
ANTISTATIC
LIGHT FASTNESS



COLOURLINE



Trent

ABBEY



776



774



775



773



772



756



748



747




749



746

HOW TO INSTALL

QUARTER TURN



BRICK

